

## **The PLASCO Line of Paint, Varnish and Enamel Products »**

### **PLASCO FLAT WALL PAINT**

A durable, soft sheen, washable wall paint for plaster, wallboard or composition walls and ceilings.

### **PLASCO FLOOR PAINT**

For all types of interior floors and woodwork — quick drying — economical.

### **PLASCO READY MIXED PAINT**

Of good quality for general exterior painting.

### **PLASCO SEMI-GLOSS ENAMEL**

A durable, washable low gloss enamel for kitchen, hall and bathroom walls and ceilings.

### **PLASCO UTILITY ENAMEL**

For furniture, woodwork, toys, farm implements — in fact, for all general purposes.

### **PLASCO VARNISH AND ENAMEL**

A complete line of medium priced varnishes for all general purposes.

### **PLASCO VARNISH STAINS**

To renew furniture and woodwork — stains and varnishes in one operation.

# PLASCO

REG. U. S. PAT. OFF.

## SEMI-GLOSS ENAMEL



PITTSBURGH  
PLATE GLASS COMPANY  
PAINT-VARNISH-LACQUER

E. J. White Paint & Glass Co.  
123 St. Paul St.-Tel. 1652  
Burlington, Vt.

# PLASCO SEMI-GLOSS ENAMEL

A durable, high-grade, easy washing, semi-gloss decorative finish suitable for all interior standing surfaces such as plaster, wood, wallboard, metal, cement, brick or masonry.

It is especially adapted for use in Schools, Hotels, Public and Office Buildings, Factories, and in the Kitchen, Bathroom, Hallway and Laundry of Residences.

Plasco Semi-Gloss Enamel dries readily with a beautiful finish that is sanitary, washable and enduring.

Plasco Semi-Gloss Enamel Colors may be mixed with each other or with white to produce a large number of pleasing combinations.



23-12  
IVORY



23-14  
SILVER GRAY



23-16  
GOLDEN BUFF



23-17  
AZURE



23-18  
CHAMOIS



23-19  
ARBOR GREEN

ALSO WHITE AND PRIMER SEALER

## DIRECTIONS

STIR CONTENTS THOROUGHLY  
FROM THE BOTTOM

**PREPARATION OF SURFACE**— Surface to be finished must be clean and dry. Wash or scrape off all calcimine, loose paint, grease and dirt. Fill plaster cracks with a stiff paste made of Plasco Primer Sealer and Plaster Paris. Smooth or glossy surfaces should be roughened with steel wool or sandpaper before refinishing.

**NEW WORK** — First Coat — For best results use Plasco Primer Sealer reduced with two pints of Leptyne or Turpentine per gallon. Use no Linseed Oil or other thinner for reducing Plasco Primer Sealer. Pittsburgh Fluid Oil Colors may be used to tint Plasco Primer Sealer to match finishing coat. As an alternate first coat, Plasco Semi-Gloss Enamel reduced with one pint of Pure Boiled Linseed Oil per gallon may be used. Allow 24 hours for drying with this system. **Finishing Coat** — Use Plasco Semi-Gloss Enamel as it comes in the can. **OLD WORK** — One coat of Plasco Semi-Gloss Enamel is sufficient over old paint in good condition where color difference is not too great. Where surface being covered is extremely dark a second coat may be necessary for complete hiding. Allow at least 24 hours for drying before applying second coat. Surfaces which have been previously stained should be given two thin coats of shellac before finishing. (ISSUED 1/15/35)

Successful Painting requires the use of a proper brush.

Use a Gold Stripe Brush.